

**Declaration of performance**  
**№ DPCTLWGL001KAIG1**

(UK)-Rev. №3

1) Unique identification code of the product-type;

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Dry-pressed ceramic tiles with low water absorption  $E_b \leq 0.5\%$ , glazed, for internal and external walls and floorings**

2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **external and internal surface finishes-floors, walls**

3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): **KAI Group: Khan Asparuh AD, Ispcrih, 1 Ahinora Str., Phone: +35984312577, Fax: +35984313613; E-mail: [info@kai.bg](mailto:info@kai.bg)**

4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*

5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*

7) Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
<b>Reaction to fire</b>	<b>Class A1fl/A1</b>	<b>EN 14411:2012</b>
<b>Release of dangerous substances:</b> - cadmium - lead - other	<b>NPD</b> <b>NPD</b> <b>NPD</b>	
<b>Breaking strength</b> -thickness $\geq 7.5\text{mm}$ -thickness $< 7.5\text{mm}$	<b><math>\geq 1300\text{N}</math></b> <b><math>\geq 700\text{N}</math></b>	
<b>Durability for:</b> - internal use - external use-freeze-thaw resistance	<b>Pass</b> <b>Pass</b>	
<b>Bond strength/adhesion</b> - cementitious adhesive - dispersion adhesive - reactive resin adhesive - mortar	<b><math>\geq 0.5\text{ N/mm}^2</math></b> <b><math>\geq 1.0\text{ N/mm}^2</math></b> <b><math>\geq 2.0\text{ N/mm}^2</math></b> <b>NPD</b>	
<b>Thermal Shock Resistance</b>	<b>Pass</b>	
<b>Tactility</b>	<b>NPD</b>	
<b>Slipperiness</b>	<b>See the table</b>	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**Ispcrih, 01.08.2021.**

