

## Declaration of performance Nº DPCTLMWGL011KAIG1

(UK)-Rev. Nº4

1)Unique identification code of the product-type;

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Dry-pressed ceramic tiles with water absorption 0,5%<E $\leq$ 3%, glazed, for iternal and external walls and floorings 2) Intended use or uses of the construction product, in accordance with the applicable harmonized technical

specification, as foreseen by the manufacturer: external and internal surface finishes, floors, walls

3) Name registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5): KAI Group: "Хан Аспарух" АД, Исперих, ул. "Ахинора" 1, България; Телефон: +35984312577; Факс: +35984313613; Е-mail: info@kai.bg

- 4) Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): *not applicable*
- 5) System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 4
- 6) In case of the declaration of performance concerning a construction product covered by a harmonized standard: Name and number of notified body: *not applicable*
- 7) Declared performance/s:

| Essential Characteristics   | Performance                                   | Harmonized technical Specification |
|---|---|------------------------------------|
| Reaction to fire  | Class A1fl/A1                                 |                                    |
| Release of dangerous substances:<br>- cadmium<br>- lead<br>- other                                      | NPD<br>NPD<br>NPD                             |                                    |
| Breaking strength<br>- thickness≥7.5mm<br>- thickness<7.5mm   | ≥1100N<br>≥700N                               |                                    |
| Durability for: - internal use: - external use: freeze-thaw resistance                                  | Pass<br>Pass                                  | EN 14411:2012                      |
| Bond strength/adhesion - cementitious adhesive - dispersion adhesive - reactive resin adhesive - mortar | ≥0.5 N/mm2<br>≥1.0 N/mm2<br>≥2.0 N/mm2<br>NPD |                                    |
| Thermal Shock Resistance  | Pass  |                                    |
| Tactility   | NPD   |                                    |
| Slipperiness  | NPD   |                                    |

Plamer

област

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Isperih, 01.07.2023.